


Smooth Spring Plunger without collar

FINISH



| FI |
|------------------------------|
| Stainless steel 1.4305 |
| Stainless steel, hardened |
| Stainless steel |

| Order No. | | D ₁ mm | S mm | D ₂ mm | L mm | F S=0 N | F Smax N |
|-----------|----|----------------------|---------|----------------------|---------|------------|-------------|
| E-210-020 | | 2 | 0.3 | 1 | 3.5 | 0.8 | 1.5 |
| E-210-025 | | 2.5 | 0.4 | 1.5 | 5 | 2.8 | 4.7 |
| E-210-030 | | 3 | 0.65 | 2 | 7 | 4.5 | 7.5 |
| E-210-035 | | 3.5 | 0.8 | 2.5 | 9 | 6 | 14.5 |
| E-210-040 | FI | 4 | 0.9 | 3 | 11 | 8 | 14 |
| E-210-045 | | 4.5 | 0.95 | 3.2 | 12 | 9.5 | 16.5 |
| E-210-050 | | 5 | 1 | 3.5 | 13 | 11 | 18 |
| E-210-055 | | 5.5 | 1.2 | 4 | 14 | 15.5 | 25 |
| E-210-060 | | 6 | 1.5 | 4.5 | 15 | 18 | 31 |

Ordering example: 4 x E-210-04-FI

